

SIZE: 5.5 in. [139.7]
 WEIGHT: 20 lbm/ft [29.76]
 GRADE: HCP-110
 CONNECTION: TTRS1
 High Collapse

Material	Imperial	Metric
Yield Stress (min) (psi [kPa])	110,000	758,423
Yield Stress (max) (psi [kPa])	140,000	965,266
Tensile Stress (min) (psi [kPa])	125,000	861,845
Hardness (max) (HRC [HBW])	N/A	N/A
Pipe Body Data		
Outside Diameter, Nominal (in [mm])	5.500	139.70
Weight, Nominal (lbm/ft [kg/m])	20.00	29.76
Wall Thickness, Nominal (in [mm])	0.361	9.17
Inside Diameter, Nominal (in [mm])	4.778	121.36
API Drift Diameter (in [mm])	4.653	118.19
Alternate Drift Diameter (in [mm])	N/A	N/A
Cross Section, Nominal (sq.in. [mm ²])	5.828	3759.99
Pipe Performance		
Tensile Yield (lbf [N])	641,100	2,851,754
Internal Yield Pressure (psi [kPa])	12,640	87,150
Collapse Pressure (psi [kPa])	13,350	92,045
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Connection Data		
Connection OD (in [mm])	6.300	160.02
Special Clearance OD (in [mm])	5.875	149.23
Connection ID (in [mm])	4.778	121.36
Coupling Length (min) (in [mm])	9.250	234.95
Make-up Loss (in [mm])	4.125	104.78
Threads per Inch (pitch [mm])	5.000	5.08
Torque Capacity		
Minimum MUT (lbf-ft [N.m])	8,200	11,120
Optimum MUT (lbf-ft [N.m])	13,900	18,850
Maximum MUT (lbf-ft [N.m])	19,600	26,570
Rotating Torque (lbf-ft [N.m])	19,600	26,570
Yield Torque (lbf-ft [N.m])	23,000	31,180

Connection Performance	
Tensile Efficiency (% of pipe Body)	100%
Internal Yield Pressure (% of pipe Body)	100%
External yield pressure (% of pipe Body)	100%
Compression Efficiency (% of pipe Body)	100%
Bending rate, pipe body (°/100 ft)	92



Connection performance and torque data have been proven by extensive laboratory and field tests.

Inspection Criteria: All the material is inspected to 5% Test notch inspection for OD/ID, Long/Trans and wall check per API/ASTM requirements though EMI/SEA.

1. Yield Torque - Beyond this value the connection will not drift with the standard API drift diameter.
2. Rotating Torque - Recommended maximum torque when rotating the string (calculated as 85% of the Yield Torque, Safety Factor = 1.176).
3. Tensile Yield - Maximum weight that can be pulled on the string.

Note: All the information provided is general data. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1 and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.

Technical Support:

8799 North Loop East, Suite 300
 Houston, TX 77029

Local: 713-631-0071 • Toll Free: 1-800-469-7549
connectionsupport@tejastubular.com

© 2019 Tejas Tubular Products, Inc.
www.tejastubular.com