

SIZE: 2.375 inch [60.33 mm]

WEIGHT: 5.95 lbm/ft [8.85 kg/m]

GRADE: P-110

Interchangeable with PH6, BTS6, RTS6, NTS6, WTS6, etc. Can be equipped with 3/4 inch wide hardband on the box or both ends

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	110,000	758,423
Yield Stress, Maximum (psi [kPa])	140,000	965,266
Tensile Stress, Minimum (psi [kPa])	125,000	861,845
Hardness, Maximum (HRC [HBW])	N/A	N/A
Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	2.375	60.33
Weight, Nominal (lbm/ft [kg/m])	5.95	8.85
Wall Thickness, Nominal (in [mm])	0.254	6.45
Inside Diameter, Nominal (in [mm])	1.867	47.42
API Drift Diameter (in [mm])	1.773	45.04
Upset-End Diameter, Minimum (in [mm])	N/A	N/A
Upset-End Length, Maximum (in [mm])	N/A	N/A
Cross Sectional Area, Nominal (sq.in. [sq.mm])	1.692	1091.61
Pipe Load Capacities		
Tensile Yield (lbf [N])	186,100	827,814
Internal Yield Pressure (psi [kPa])	20,590	141,963
Collapse Pressure (psi [kPa])	21,010	144,859
Torsional Yield (lbf-ft [N.m])	8,600	11,660
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Bending rate (°/100 ft [°/30 m])	212	209
Connection Dimensions		
Coupling OD (in [mm])	2.906	73.81
Special Clearance** OD (in [mm])	2.782	70.66
Connection ID (in [mm])	1.805	45.85
Tool-Joint Length (in [mm])	9.000	228.60
Make-up Loss (in [mm])	3.056	77.62
Threads per Inch (pitch [mm])	6.000	4.23
Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	490	660
High Shoulder Torque (lbf-ft [N.m])	2,450	3,320
Minimum Make-up Torque (lbf-ft [N.m])	2,700	3,660
Optimum Make-up Torque (lbf-ft [N.m])	3,100	4,200
Maximum Make-up Torque (lbf-ft [N.m])	3,400	4,610
Rotating Torque* (lbf-ft [N.m])	6,400	8,680
Yield Torque (lbf-ft [N.m])	8,000	10,850

\* AS RESTRICTED BY WORKOVER RIG EQUIPMENT (POWER SWIVEL, TOP DRIVE OR ROTARY TABLE)

\*\* Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.

Material is EMI/SEA inspected to 5% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTRS1-HT, TTXS, TTXS-HT, TTNY, TTNY-HP, TTUS, TTUS-HT, TTU, TTS-8 CI, TTS-8 CIGL, TTS-8s, TTS-6, TTS6-black, TTIB, TTFJ, TTU, TTWS, TTWSs, TTWS2, TTWS-U, SABERTOOTH, GOBLIN, EUXT and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.

Connection Load Capacities	
Tensile Efficiency (% of pipe body)	125
Internal Yield Pressure (% of pipe body)	100
External Yield pressure (psi)	33,780
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	125
Torque Efficiency (% of pipe body)	93
Bending Strength Ratio (BSR)	1.83

