

SIZE: 2.875 inch [73.03 mm]

WEIGHT: 7.9 lbm/ft [11.76 kg/m]

GRADE: TT-125

TEJAS proprietary grade, equivalent and even superior to API Q Interchangeable with PH6, BTS6, RTS6, NTS6, WTS6, etc. Can be equipped with 3/4 inch wide hardband on the box or

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	125,000	861,845
Yield Stress, Maximum (psi [kPa])	150,000	1,034,214
Tensile Stress, Minimum (psi [kPa])	135,000	930,792
Hardness, Maximum (HRC [HBW])	N/A	N/A

Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	2.875	73.03
Weight, Nominal (lbm/ft [kg/m])	7.90	11.76
Wall Thickness, Nominal (in [mm])	0.276	7.01
Inside Diameter, Nominal (in [mm])	2.323	59.00
API Drift Diameter (in [mm])	2.229	56.62
Upset-End Diameter, Minimum (in [mm])	N/A	N/A
Upset-End Length, Maximum (in [mm])	N/A	N/A
Cross Sectional Area, Nominal (sq.in. [sq.mm])	2.254	1454.19

Pipe Load Capacities		
Tensile Yield (lbf [N])	281,800	1,253,508
Internal Yield Pressure (psi [kPa])	21,000	144,790
Collapse Pressure (psi [kPa])	21,700	149,616
Torsional Yield (lbf-ft [N.m])	16,090	21,820
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Bending rate (°/100 ft [°/30 m])	199	196

Connection Dimensions		
Coupling OD (in [mm])	3.438	87.33
Special Clearance** OD (in [mm])	3.312	84.12
Connection ID (in [mm])	2.265	57.53
Tool-Joint Length (in [mm])	9.000	228.60
Make-up Loss (in [mm])	3.040	77.22
Threads per Inch (pitch [mm])	6.000	4.23

Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	650	880
High Shoulder Torque (lbf-ft [N.m])	3,250	4,410
Minimum Make-up Torque (lbf-ft [N.m])	3,500	4,750
Optimum Make-up Torque (lbf-ft [N.m])	4,000	5,420
Maximum Make-up Torque (lbf-ft [N.m])	4,400	5,970
Rotating Torque* (lbf-ft [N.m])	10,800	14,640
Yield Torque (lbf-ft [N.m])	13,500	18,300

* AS RESTRICTED BY WORKOVER RIG EQUIPMENT (POWER SWIVEL, TOP DRIVE OR ROTARY TABLE)

** Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.

Material is EMI/SEA inspected to 5% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTRS1-HT, TTXS, TTXS-HT, TTTY, TTTY-HP, TTUS, TTUS-HT, TTUX, TTS-8, TTS-8 CI, TTS-8 CIGL, TTS-8s, TTS-6, TTS6-black, TTIB, TTFJ, TTIJ, TTWS, TTWSs, TTWS2, TTWS-IJ, SABERTOOTH, GOBLIN, EUXT and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.

Connection Load Capacities	
Tensile Efficiency (% of pipe body)	116
Internal Yield Pressure (% of pipe body)	100
External Yield pressure (psi)	35,370
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	116
Torque Efficiency (% of pipe body)	84
Bending Strength Ratio (BSR)	1.71

