

SIZE: 3.5 inch [88.9 mm]

WEIGHT: 12.95 lbm/ft [19.27 kg/m]

GRADE: P-110

Interchangeable with PH6, BTS6, RTS6, NTS6, WTS6, etc. Can be equipped with 3/4 inch wide hardband on the box or both ends

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	110,000	758,423
Yield Stress, Maximum (psi [kPa])	140,000	965,266
Tensile Stress, Minimum (psi [kPa])	125,000	861,845
Hardness, Maximum (HRC [HBW])	N/A	N/A
Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	3.500	88.90
Weight, Nominal (lbm/ft [kg/m])	12.95	19.27
Wall Thickness, Nominal (in [mm])	0.375	9.53
Inside Diameter, Nominal (in [mm])	2.750	69.85
API Drift Diameter (in [mm])	2.625	66.68
Upset-End Diameter, Minimum (in [mm])	N/A	N/A
Upset-End Length, Maximum (in [mm])	N/A	N/A
Cross Sectional Area, Nominal (sq.in. [sq.mm])	3.682	2375.48
Pipe Load Capacities		
Tensile Yield (lbf [N])	405,000	1,801,529
Internal Yield Pressure (psi [kPa])	20,630	142,239
Collapse Pressure (psi [kPa])	21,050	145,135
Torsional Yield (lbf-ft [N.m])	27,560	37,370
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Bending rate (°/100 ft [°/30 m])	144	142
Connection Dimensions		
Coupling OD (in [mm])	4.313	109.55
Special Clearance** OD (in [mm])	4.189	106.40
Connection ID (in [mm])	2.687	68.25
Tool-Joint Length (in [mm])	9.000	228.60
Make-up Loss (in [mm])	3.350	85.09
Threads per Inch (pitch [mm])	6.000	4.23
Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	1,350	1,830
High Shoulder Torque (lbf-ft [N.m])	6,750	9,150
Minimum Make-up Torque (lbf-ft [N.m])	7,000	9,490
Optimum Make-up Torque (lbf-ft [N.m])	7,875	10,680
Maximum Make-up Torque (lbf-ft [N.m])	8,750	11,860
Rotating Torque* (lbf-ft [N.m])	22,600	30,640
Yield Torque (lbf-ft [N.m])	28,200	38,230

* AS RESTRICTED BY WORKOVER RIG EQUIPMENT (POWER SWIVEL, TOP DRIVE OR ROTARY TABLE)

** Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.

Material is EMI/SEA inspected to 5% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTRS1-HT, TTXS, TTXS-HT, TTNY, TTNY-HP, TTUS, TTUS-HT, TTXU, TTS-8, TTS-8 CI, TTS-8 CIGL, TTS-8s, TTS-6, TTIB, TTIJ, EUXT, SABERTOOTH, TTFJ, TTWS, TTS6-Black, GOBLIN, SPEARHEAD and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.

Connection Load Capacities	
Tensile Efficiency (% of pipe body)	137
Internal Yield Pressure (% of pipe body)	100
External Yield pressure (psi)	33,650
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	137
Torque Efficiency (% of pipe body)	102
Bending Strength Ratio (BSR)	1.53

