

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	110,000	758,423
Yield Stress, Maximum (psi [kPa])	140,000	965,266
Tensile Stress, Minimum (psi [kPa])	125,000	861,845
Hardness, Maximum (HRC [HBW])	N/A	N/A
Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	2.875	73.03
Weight, Nominal (lbm/ft [kg/m])	7.90	11.76
Wall Thickness, Nominal (in [mm])	0.276	7.01
Inside Diameter, Nominal (in [mm])	2.323	59.00
API Drift Diameter (in [mm])	2.229	56.62
Upset-End Diameter, Minimum (in [mm])	N/A	N/A
Upset-End Length, Maximum (in [mm])	N/A	N/A
Cross Sectional Area, Nominal (sq.in. [sq.mm])	2.254	1454.19
Pipe Load Capacities		
Tensile Yield (lbf [N])	247,900	1,102,714
Internal Yield Pressure (psi [kPa])	18,480	127,415
Collapse Pressure (psi [kPa])	19,090	131,621
Torsional Yield (lbf-ft [N.m])	14,160	19,200
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Bending rate (°/100 ft [°/30 m])	175	173
Connection Dimensions		
Connection OD (in [mm])	3.525	89.54
Special Clearance** OD (in [mm])	3.312	84.12
Connection ID (in [mm])	2.265	57.53
Tool-Joint Length (in [mm])	9.000	228.60
Make-up Loss (in [mm])	2.991	75.97
Threads per Inch (pitch [mm])	6.000	4.23
Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	300	410
High Shoulder Torque (lbf-ft [N.m])	1,500	2,030
Minimum Make-up Torque (lbf-ft [N.m])	2,000	2,710
Optimum Make-up Torque (lbf-ft [N.m])	4,250	5,760
Maximum Make-up Torque (lbf-ft [N.m])	6,500	8,810
Rotating Torque* (lbf-ft [N.m])	13,900	18,850
Yield Torque (lbf-ft [N.m])	15,400	20,880

* AS RESTRICTED BY WORKOVER RIG EQUIPMENT (POWER SWIVEL, TOP DRIVE OR ROTARY TABLE)

** Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.

Material is EMI/SEA inspected to 5% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

SIZE: 2.875 inch [73.03 mm]

WEIGHT: 7.9 lbm/ft [11.76 kg/m]

GRADE: P-110

Double-Shoulder = Ultra High Torque, Deep-Stabbing = Self-Aligning, Double-Start = Fast-Makeup, Hook-Thread = No-Jumpouts, Single or Double Hardbanded = Xtra-Long Wear-Life, equipped with 3/4 inch wide hardband on box or both ends

Connection Load Capacities

Tensile Efficiency (% of pipe body)	122
Internal Yield Pressure (psi)	34,400
External Yield pressure (psi)	32,290
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	122
Torque Efficiency (% of pipe body)	109
Bending Strength Ratio (BSR)	1.25



All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTRS1-HT, TTXS, TTXS-HT, TTUS, TTUS-HT, TTXU, TTS-8, TTS-8 CI, TTS-8 CIGL, TTS-6, TTS6-Black, TTIB, TTUJ, TTFJ, TTWS, TTWS-Black, SABERTOOTH, GOBLIN, SPEARHEAD, EUXT and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.