

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	80,000	551,581
Yield Stress, Maximum (psi [kPa])	95,000	655,002
Tensile Stress, Minimum (psi [kPa])	95,000	655,002
Hardness, Maximum (HRC [HBW])	23	241
Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	2.875	73.03
Weight, Nominal (lbm/ft [kg/m])	6.50	9.67
Wall Thickness, Nominal (in [mm])	0.217	5.51
Inside Diameter, Nominal (in [mm])	2.441	62.00
API Drift Diameter (in [mm])	2.347	59.62
Upset-End Diameter, Minimum (in [mm])	3.329	84.56
Upset-End Length, Minimum (in [mm])	4.250	107.95
Cross Sectional Area, Nominal (sq.in. [sq.mm])	1.812	1169.03
Pipe Load Capacities		
Tensile Yield (lbf [N])	145,000	644,992
Internal Yield Pressure (psi [kPa])	10,570	72,878
Collapse Pressure (psi [kPa])	11,170	77,014
Torsional Yield (lbf-ft [N.m])	8,620	11,690
Hydrostatic Test Pressure (psi [kPa])	9,700	66,879
Bending rate (°/100 ft [°/30 m])	128	126
Connection Dimensions		
Connection OD (in [mm])	3.210	81.53
Special Clearance** OD (in [mm])	3.166	80.42
Connection ID (in [mm])	2.366	60.10
Coupling Length, Minimum (in [mm])	N/A	N/A
Make-up Loss (in [mm])	2.390	60.71
Threads per Inch (pitch [mm])	8.000	3.18
Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	370	500
High Shoulder Torque (lbf-ft [N.m])	1,850	2,510
Minimum Make-up Torque (lbf-ft [N.m])	2,100	2,850
Optimum Make-up Torque (lbf-ft [N.m])	2,400	3,250
Maximum Make-up Torque (lbf-ft [N.m])	2,600	3,530
Rotating Torque (lbf-ft [N.m])	5,500	7,460
Yield Torque (lbf-ft [N.m])	6,900	9,360

\*\* Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.  
 Material is EMI/SEA inspected to 10% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTRS1-HT, TTXS, TTXS-HT, TTUS, TTUS-HT, TTU, TTS-8, TTS-8 CI, TTS-8 CIGL, TTS-6, TTS6-Black, TTIB, TTUJ, TTFJ, TTWS, TTWS-Black, SABERTOOTH, GOBLIN, SPEARHEAD, EUXT and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.

SIZE: 2.875 inch [73.03 mm]  
 WEIGHT: 6.5 lbm/ft [9.67 kg/m]  
 GRADE: L-80

CS look-alike, with an internal corrosion inhibitor coating, reinforced by fiberglass liner and a teflon seal ring, for highly corrosive sour/sweet applications, in which you want a ruggedized ID

Connection Load Capacities	
Tensile Efficiency (% of pipe body)	118
Internal Yield Pressure (% of pipe body)	100
External Yield pressure (psi)	18,270
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	118
Torque Efficiency (% of pipe body)	80
Bending Strength Ratio (BSR)	1.30

