

Material Properties	Imperial	Metric
Yield Stress, Minimum (psi [kPa])	110,000	758,423
Yield Stress, Maximum (psi [kPa])	140,000	965,266
Tensile Stress, Minimum (psi [kPa])	125,000	861,845
Hardness, Maximum (HRC [HBW])	N/A	N/A
Pipe Dimensions & Weight		
Outside Diameter, Nominal (in [mm])	2.875	73.03
Weight, Nominal (lbm/ft [kg/m])	9.50	14.14
Wall Thickness, Nominal (in [mm])	0.340	8.64
Inside Diameter, Nominal (in [mm])	2.195	55.75
API Drift Diameter (in [mm])	2.101	53.37
Upset-End Diameter, Minimum (in [mm])	N/A	N/A
Upset-End Length, Maximum (in [mm])	N/A	N/A
Cross Sectional Area, Nominal (sq.in. [sq.mm])	2.708	1747.09
Pipe Load Capacities		
Tensile Yield (lbf [N])	297,900	1,325,125
Internal Yield Pressure (psi [kPa])	22,770	156,994
Collapse Pressure (psi [kPa])	22,940	158,166
Torsional Yield (lbf-ft [N.m])	16,290	22,090
Hydrostatic Test Pressure (psi [kPa])	10,000	68,948
Bending rate (°/100 ft [°/30 m])	175	173
Connection Dimensions		
Coupling OD (in [mm])	3.525	89.54
Coupling Replacement Limit OD (in [mm])	3.400	86.36
Connection ID (in [mm])	2.265	57.53
Coupling Length, Minimum (in [mm])	6.800	172.72
Make-up Loss (in [mm])	2.991	75.97
Tool-Joint OD (in [mm])	3.338	84.79
Connection Torque Capacities		
Low Shoulder Torque (lbf-ft [N.m])	300	410
High Shoulder Torque (lbf-ft [N.m])	1,500	2,030
Minimum Make-up Torque (lbf-ft [N.m])	2,000	2,710
Optimum Make-up Torque (lbf-ft [N.m])	4,250	5,760
Maximum Make-up Torque (lbf-ft [N.m])	6,500	8,810
Rotating Torque* (lbf-ft [N.m])	13,800	18,710
Yield Torque (lbf-ft [N.m])	15,300	20,740

\* AS RESTRICTED BY WORKOVER RIG EQUIPMENT (POWER SWIVEL, TOP DRIVE OR ROTARY TABLE)

\*\* Listed Rotating / Yield Torques and Connection Load Capacities have to be recalculated for Special Clearance OD.

Material is EMI/SEA inspected to 5% notch, over OD/ID, long/trans and wall thickness orientations, per API/ASTM requirements.

SIZE: 2.875 inch [73.03 mm]

WEIGHT: 9.5 lbm/ft [14.14 kg/m]

GRADE: P-110

Double-Shoulder = Ultra High Torque, Deep-Stabbing = Self-Aligning, Double-Start = Fast-Makeup, Hook-Thread = No-Jumpouts, Replaceable Coupling = Xtra-Long Wear-Life

### Connection Load Capacities

Tensile Efficiency (% of pipe body)	102
Internal Yield Pressure (psi)	34,400
External Yield pressure (psi)	32,290
Leak Resistance Pressure (psi)	radial m2m seal
Compression Efficiency (% of pipe body)	102
Torque Efficiency (% of pipe body)	94
Bending Strength Ratio (BSR)	1.25



All the information provided is general data. Depicted colors and markings may differ from actual product. This is not any kind of warranty/quality certificate. Tejas Tubular has the right to change this data at any time for product improvement. This is a non-controlled document. TTRS1, TTXS, TTUS, TTUS-HT, TTNV, TTXU, TTS8, TTS8 CI, TTS8 CIGL, TTS6, TTS6-Black, TTIB, TTUJ, TTFJ, TTWS, SABERTOOTH, GOBLIN, SPEARHEAD, CERBERUS, EUXT, WS-WATE and the Tejas Tubular logo are marks of Tejas Tubular Products, Inc.